





Snapscan here to pay

Cutsmart.co.za TAX INVOICE

VAT No: 4500272291 Account: FNB 6257 0589 691 Branch no. 250 102 Use Ref. {order_number}

TEL: 087 094 8794

Makita DUN461W Cordless Pole Hedge Trimmer



Excludes Battery 18V LXT Cordless 46 cm Pole Hedge Trimmer BritisegriNetvRthtedxN&19710.96 Salesprice with discount Sales price R 9710.96

Ask a question about this product Manufacturer Makita

Disscriptibedges or prune the twigs or thin branches of tall trees without using stepladder High cutting speed enables smooth and efficient trimming Low noise level similar or lower than that of the competitors 3,600 SPM for faster cutting

Telescopic pipe for no need of stepladders

New chip receiver can make it easier for user to collect leaf and twig debris,

thanks to lower height of the connecting hooks and reduced step height of the edge of the chip catching plate Lock lever for tool-less easy adjustment of pole extension

Ballito	Empangeni	Hilton	Mtubatuba	1
2 Lemon Reef	50 Tanner Rd	Shop 14	Shop2 Oriol Ctr	Received by
20 Douglas Crowe	Empangeni Rail	Hilton Siding	30 Jan Smuts Ave	
Ballito	Empangeni	Hilton	Mtubatuba	Name:
KZN 4420	KZN 3880	KZN 3201	KZN 3935	
bal@cutsmart.co.za	emp@cutsmart.co.za	hil@cutsmart.co.za	mtu@cutsmart.co.za	Sign:

CUTSMART www.cutsmart.co.za Roto: C. Britter / Proventer Products 087 094 8794

Thank you for your Support!



Snapscan here to pay

Cutsmart.co.za TAX INVOICE

VAT No: 4500272291 Account: FNB 6257 0589 691 Branch no. 250 102 Use Ref. {order_number}

TEL: 087 094 8794

Slide-type front grip grip position is adjustable for personal fit and comfort maximum work efficiency in different working postures

Angle adjustable hedge trimmer head; 60° tilt-up to 75° tilt-down from the horizontal position; Can be folded in the 180° position for easy transport and storage; Built-in clutch works to stop the blade motion even if the throttle lever is touched during folding operation; 10 angle settings; The angle of hedge trimmer head can be changed simply by pushing a button

Reverse rotation system frees the blade when it is jammed by thick branches

Lock-off button accessible from both sides

Single-speed switch

Battery guard

Battery protection circuit protects against overloading, over-discharging and over-heating

Cordless for instant start-up, zero emissions and reduced maintenance

Extreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions

Blade Length:
460 mm (18-1/8?)
Tooth Spacing:
28 mm (1-1/8?)
Max Cutting Capacity:
18 mm (11/16?)

Strokes Per Minute (SPM):

3,600

Continuous Use (min.):

w/ BL1850B: 122 Max Output:

250 W

Sound Pressure Level:

74 dB(A)

Noise K Factor:

3 dB(A)

Vibration Level:

Front / Rear: 2.5 m/s² / 2.5 m/s² or less

Vibration K Factor:

1.5 m/s²

Dimensions (L x W x H):

1,889 – 2,511 x 87 x 134 mm (74-1/2 – 99 x 3-7/16 x 5-1/4?)

Net weight:

3.0 – 3.3 kg (6.6 – 7.3 lbs.)